TM12E/TM16E ELECTRIC DRIVE TELESCOPIC MAST LIFTS



- Industry-leading electric drive telescopic mast lifts
- Versatile, robust and simple to use
- Drives through a standard doorway
- Smooth & efficient electric drive
- Ideal for many applications from construction to stockpicking



ELECTRIC DRIVE TELESCOPIC MAST LIFTS

| DIMENSIONS | TM12E | TM16E |
|---------------------------------------|---------------|---------------|
| Max. working height | 5.65m | 6.87m |
| Max. platform height (A) | 3.65m | 4.87m |
| Platform size (stowed) | 0.68m x 0.99m | 0.68m x 0.99m |
| Platform size (extended) (E) | 0.68m x 1.5m | 0.68m x 1.5m |
| Deck extension length | 0.51m | 0.51m |
| Overall width (B) | 0.76m | 0.76m |
| Overall length (D) | 1.37m | 1.37m |
| Stowed height (C) | 1.67m | 1.98m |
| Ground clearance | 76mm | 76mm |

PERFORMANCE

| 227kg | 227kg |
|--|---|
| 3.65m | 4.87m |
| 12.5m/s | 0m/s |
| 4.0km/h | 4.0km/h |
| 0.6km/h | 0.6km/h |
| 19/17 sec | 28/36 sec |
| 25% | 25% |
| 2° | 1.5° |
| 2° | 1.5° |
| 0m | 0m |
| 1.4m | 1.4m |
| 323mm non-marking rubber | |
| 2-wheel, spring applied, electric release | |
| dual DC motors | |
| proportional | |
| | 3.65m 12.5m/s 4.0km/h 0.6km/h 19/17 sec 25% 2° 2° 0m 1.4m 323mm non-ma 2-wheel, sprin electric r dual DC r |


POWER

| Power source | 24V 220Ah batteries | |
|-----------------|---------------------|--------|
| Battery charger | 20 amp | 20 amp |

WEIGHT

| Weight | 1,016kg |
|--------|---------|
| | |


TURNING RADIUS



ANSI Specification © Snorkel 2021

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate Snorkel operators manual for detailed instructions on the proper use and maintenance

TM12E/TM16E



STANDARD FEATURES

- Zero inside turning radius
- Roll-out deck extension •
- Proportional controls •
- Saloon-door style entry gates
- Descent & tilt alarms •
- Emergency lowering at chassis controls •
- Non-marking rubber tires •
- Crane lift points •
- Horn •
- 2 persons indoor
- 1 person outdoor (TM12E only) •
- Selectable motion alarm •
- Integrated battery charger 110V 20A •
- Hour meter & on-board diagnostics display •
- Platform overload system •
- 2 year parts & labor, 5 year structural warranty •
- ANSI compliant

OPTIONS

1,105kg

- Special paint colors
- . Environmental hydraulic oil
- Order picker tray (TM12E only) •
- Snorkel OnSite[™] telematics •



P.O. Box 1160 St.Joseph, MO 64502-1160, USA Tel: 1 (785) 989-3000 Toll-free: 1 (800) 255-0317 Fax: 1 (785) 989-3070 Email: sales.usa@snorkellifts.com

02/2021